

Helipur

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Helipur

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Disinfection and cleaning of medical instruments, laboratory equipment, surfaces and excrements

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: B. Braun Medical AG
Street: Seesatz 17
Place: CH-6204 Sempach
Responsible Department: Telephone: +41 (0) 58 / 258 50 00
E-Mail: info.bbmch@bbraun.com
Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: B. Braun Melsungen AG
Street: Carl-Braun-Straße 1
Place: D-34212 Melsungen
Responsible Department: Zentrale Service-Bereiche / Logistik und Supply Chain
Telephone: +49 (0) 5661 / 71-4422
E-Mail: logistics.service@bbraun.com

1.4. Emergency telephone number: INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 3

Substance or mixture corrosive to metals: Met. Corr. 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Flammable liquid and vapour.

May be corrosive to metals.

Harmful if swallowed or in contact with skin.

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

4-Chloro-3-methylphenol

2-Benzyl-4-chlorophenol

Sodium hydroxide

Signal word:

Danger

Pictograms:



Helipur

Revision date: 01.06.2015

Revision No: 1,4

Product code: 00056-0013

Hazard statements

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302+H312	Harmful if swallowed or in contact with skin.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

Additional advice on labelling

In accordance with section 1.5.2 of Annex I of the European Regulation (EC) No 1272/2008, following H and P statements may be omitted for containers < 125 ml: H226, H290, H312+H332, H315, H410, P210, P260, P273

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alkaline concentrate with sodium salts from phenolic derivates

Helipur

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
68188-18-1	Paraffin oils, sulfochlorinated, saponified			15 - 30 %
	269-144-1		01-2119517577-32	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
67-63-0	Propan-2-ol			< 15 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
59-50-7	4-Chloro-3-methylphenol			8,5 %
	200-431-6	604-014-00-3	01-2119938953-25	
	Acute Tox. 4, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H312 H318 H317 H400			
120-32-1	2-Benzyl-4-chlorophenol			4,8 %
	204-385-8			
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1B, STOT RE 2, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 10); H332 H315 H318 H317 H373 H400 H410			
90-43-7	Biphenyl-2-ol			4 %
	201-993-5	604-020-00-6	01-2119511183-53	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Acute 1; H315 H319 H335 H400			
68891-38-3	Alcohols, C12-14, ethoxylated, sulfates, sodium salts			1 - 5 %
	500-223-8			
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
1310-73-2	Sodium hydroxide			< 1 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult a physician.
Seek medical treatment by eye specialist.

After ingestion

Do not provoke vomiting. Consult physician. Attention in case of vomiting - acute danger of suffocating, produced by foaming ingredients. Rinse mouth. Make drink some glasses of water. The decision whether to provoke vomiting is to be taken by a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
Harmful in contact with skin and if swallowed.
May cause an allergic skin reaction.

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Attention. Phenols in high amounts cause local anesthetic effects so that pain due to burns may be delayed.
Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide, sulphur oxides, nitrogen oxides (NO_x), hydrochloric acid gas and phosphorus pentoxide.

Chlorine compounds.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Do not use metal containers.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation.

Keep container tightly closed in a dry, cool and well-ventilated place.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.

Do not smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Helipur

Do not use metallic container.

Advice on storage compatibility

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Disinfection and cleaning of medical instruments, laboratory equipment, surfaces and excrements

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
1310-73-2	Sodium hydroxide	-	-		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Avoid contact with skin, eyes and clothing.

Eye/face protection

Safety goggles with side protection (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Red
Odour:	Alcoholic

pH-Value (at 20 °C): approx. 11 Concentrate

Changes in the physical state

Flash point:	32 °C	DIN 51755
Lower explosion limits:	2 vol. %	

Helipur

Revision date: 01.06.2015

Revision No: 1,4

Product code: 00056-0013

Upper explosion limits:

Ignition temperature:	425 °C
Density (at 20 °C):	1,09 g/cm ³
Water solubility: (at 20 °C)	Miscible
Solvent content:	< 15 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids.

May be corrosive to metals.

10.4. Conditions to avoid

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Gives off hydrogen by reaction with metals.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide, sulphur oxides, nitrogen oxides (NOX), hydrochloric acid gas and phosphorus pentaoxide.

Chlorine compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed or in contact with skin.

No toxicological data available.

Irritation and corrosivity

Causes serious eye damage.

Causes skin irritation.

Sensitising effects

May cause an allergic skin reaction. (4-Chloro-3-methylphenol), (2-Benzyl-4-chlorophenol)

May cause an allergic skin reaction.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of vapours in high concentration can cause narcotic effects.

Risk of dangerous resorption through skin.

Helipur

Revision date: 01.06.2015

Revision No: 1,4

Product code: 00056-0013

Watch out. Beware, hazard of foam aspiration.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
120-32-1	2-Benzyl-4-chlorophenol				
	Ready Biodegradability - CO2 Evolution Test	68%		28	OECD 301B
	Not readily biodegradable.				

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Ecological injuries are not known or expected under normal use.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 2924

14.2. UN proper shipping name:

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sodium hydroxide)

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3+8

Helipur

Revision date: 01.06.2015

Revision No: 1,4

Product code: 00056-0013



Classification code: FC
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 38
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sodium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3+8



Classification code: FC
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sodium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3+8



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-C

Air transport (ICAO)

14.1. UN number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sodium hydroxide, Solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3+8



Limited quantity Passenger: 1 L
Passenger LQ: Y342
Excepted quantity: E1
IATA-packing instructions - Passenger: 354
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 365

Helipur

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)