



- light source**
- work equipment**
- connected load**
- secondary tension**
- power consumption**
- sec. power consumption**
- luminous flux**
- luminous efficiency**
- light type/-color**
- colour temperatur**
- color rendering index**
- light distribution**
- direct ratio**
- beam angle**
- chromaticity tolerance LED**
- luminance (L65)**
- unified glare rating (4H 8H)**
- system of protection**
- class of protection**
- technology**
- operation**
- housing**
- cover**
- arm**
- balance of articulation joints**
- weight (net)**
- mains lead**
- fastening**
- decorative contrast side parts**

- LED
- electronic transformer
- 100 - 240 V; Wechselstrom (AC); 50 Hz; 60 Hz
- 24 V
- ca. 27 W
- ca. 24 W
- approx. 1.300 lm
- approx. 54 lm/W
- D50 standard light; cold white
- approx. 5.000 K
- CRI > 95; R9 > 85
- direct
- approx. 100 %
- 110°
- < 3 SDCM
- <= 23000 cd/m²
- <= 28
- IP 20
- I with plug-in power supply; III without plug-in power supply
- Touch DIM
- multi-function switch
- aluminium coloured anodised
- milky; plastic
- silver metallic
- spring
- ca. 1,9 kg
- ca. 3,4 m; mains plug; CEE 7/VII
- table base
- black

