

Safety Data Sheet

according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Further trade names

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

UFI: ASAP-26DN-NX09-FR2F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

Ultrasonic Non-Ammoniated Clock Cleaning Solution

Reserved for industrial and professional use.

Uses advised against

Only use for the intended purpose.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: L&R Manufacturing Company
Street: 577 Elm Street, P.O. Box 607
Place: Kearny, NJ 07032-0607 USA

Supplier

Company name: Beco Technic GmbH
Street: Hermsdorfer Straße 5
Place: D-21502 Geesthacht
Telephone: +49 4152 80960

e-mail (Contact person): service@beco-technic.com
Internet: http://www.beco-technic.com

1.4. Emergency telephone Giftnotrufzentrale Nord: Aus dem Ausland / From abroad:+49 551-19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Acute Tox. 4; H332 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H336 STOT RE 1; H372 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 2 of 14

Hazard components for labelling

stoddard solvent

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

propan-1-ol 2-aminoethanol 2,2'-iminodiethylamine

Signal word: Danger

Pictograms:











Hazard statements

H226 Flammable liquid and vapour. Harmful if inhaled. H332 Causes skin irritation. H315 H318 Causes serious eye damage. H317 May cause an allergic skin reaction. May cause drowsiness or dizziness. H336 H372 Causes damage to organs (central nervous system) through prolonged or repeated exposure if inhaled. H304 May be fatal if swallowed and enters airways.

Precautionary statements

H411

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P260 Do not breathe fume/gas/mist/vapours/spray.
P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Toxic to aquatic life with long lasting effects.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national disposal regulations.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 3 of 14

Hazardous components

| CAS No | Chemical name | | | Quantity |
|-----------|--|---|--------------------------|----------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No | 1272/2008) | | |
| 8052-41-3 | stoddard solvent; Low boiling poir | nt naphtha - unspecified | | 60-70 % |
| | 232-489-3 | 649-345-00-4 | 01-2120261965-45 | |
| | Flam. Liq. 3, Skin Irrit. 2, STOT R H412 | E 1, Asp. Tox. 1, Aquatic Chronic 3; | H226 H315 H372 H304 | |
| | Hydrocarbons, C7-C9, n-alkanes, | isoalkanes, cyclics | | 15-25 % |
| | 920-750-0 | | 01-2119473851-33 | |
| | Flam. Liq. 2, STOT SE 3, Asp. To | x. 1, Aquatic Chronic 2; H225 H336 | H304 H411 EUH066 | |
| 2807-30-9 | 2-(propyloxy)ethanol; EGPE | | 1-5 % | |
| | 220-548-6 | 603-095-00-2 | | |
| | Flam. Liq. 3, Acute Tox. 4, Eye Irr | it. 2; H226 H312 H319 | | |
| 71-23-8 | propan-1-ol; n-propanol | | 1-5 % | |
| | 200-746-9 | 603-003-00-0 | | |
| | Flam. Liq. 2, Eye Dam. 1, STOT S | SE 3; H225 H318 H336 | | |
| 141-43-5 | 2-aminoethanol; ethanolamine | | | 1-4 % |
| | 205-483-3 | 603-030-00-8 | | |
| | Acute Tox. 4, Acute Tox. 4, Acute Aquatic Chronic 3; H332 H312 H3 | Tox. 4, Skin Corr. 1B, Eye Dam. 1, 802 H314 H318 H317 H335 H412 | Skin Sens. 1, STOT SE 3, | |
| 111-40-0 | 2,2'-iminodiethylamine; diethylene | triamine | | <1 % |
| | 203-865-4 | 612-058-00-X | | |
| | Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H318 H317 H335 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|-----------|--|---|----------|--|
| | Specific Conc. | Limits, M-factors and ATE | | |
| 2807-30-9 | 220-548-6 | 2-(propyloxy)ethanol; EGPE | 1-5 % | |
| | dermal: ATE = | 1100 mg/kg | | |
| 141-43-5 | 205-483-3 | 2-aminoethanol; ethanolamine | 1-4 % | |
| | | E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = al: ATE = 500 mg/kg STOT SE 3; H335: >= 5 - 100 | | |
| 111-40-0 | 203-865-4 | 2,2'-iminodiethylamine; diethylenetriamine | <1 % | |
| | inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 1045 mg/kg; oral: LD50 = 1553 mg/kg | | | |

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aromatic hydrocarbons, 15 % - < 30 % aliphatic hydrocarbons.

Further Information

stoddard solvent; Low boiling point naphtha - unspecified: Note P

The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301+P310-P331 shall apply.

2-aminoethanol; ethanolamine: skin sens. 1; H317 - Classification procedure: according to TGRS 907 in Germany



Safety Data Sheet

according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 4 of 14

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing. Call a physician immediately.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

Do NOT induce vomiting.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately. Aspiration hazard.

Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

Already the smallest quantities that enter the lungs during ingestion or subsequent vomiting, can lead to pulmonary edema or pneumonia.

The following symptoms may occur: diarrhea. Nausea.

Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). BC powder. ABC powder. Use water spray jet to protect personnel and to cool endangered containers.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour. Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

Closed containers may burst when pressure and temperature rise

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx).

Irritating/poisonous gasses and vapours

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 5 of 14

General advice

Do not breathe fume/gas/mist/vapours/spray. Provide adequate ventilation.

Keep away from sources of ignition - No smoking.

Use explosion-proof equipment. Use non-sparking tools.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). (caution, fire hazard)

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal precautions: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe fume/gas/mist/vapours/spray. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing.

Wear personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use explosion-proof equipment. Use non-sparking tools. Ground and bond container and receiving equipment.

Advice on general occupational hygiene

Change contaminated clothing. Take off immediately all contaminated clothing and wash it before reuse. Wash hands before breaks and after work. When using do not eat or drink. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place. Keep locked up. storage temperature: 3,9°C -37,8°C

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 6 of 14

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|-----------|-------------------------|-----|-------|---------|---------------|--------|
| 111-40-0 | 2,2-Diaminodiethylamine | 1 | 4 | | TWA (8 h) | |
| 141-43-5 | 2-Aminoethanol | 1 | 2.5 | | TWA (8 h) | |
| | | 3 | 7.6 | | STEL (15 min) | |
| 71-23-8 | n-Propanol | 100 | - | | TWA (8 h) | |
| 8052-41-3 | Stoddard solvent | 100 | 573 | | TWA (8 h) | |

DNEL/DMEL values

| CAS No | Substance | | | |
|------------|---|------------|----------|-------------------------|
| DNEL type | DNEL type | | Effect | Value |
| 8052-41-3 | stoddard solvent; Low boiling point naphtha - unspecified | | | |
| Worker DNE | , long-term | inhalation | systemic | 44 mg/m³ |
| Worker DNE | _, acute | inhalation | systemic | 55 mg/m³ |
| Worker DNE | _, long-term | inhalation | local | 44 mg/m³ |
| Worker DNE | _, acute | inhalation | local | 55 mg/m³ |
| Worker DNE | _, long-term | dermal | systemic | 80 mg/kg bw/day |
| Worker DNE | _, acute | dermal | systemic | 30 mg/kg bw/day |
| Worker DNE | _, long-term | dermal | local | 7,56 mg/cm ² |
| | Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | | | |
| Worker DNE | ., long-term | inhalation | systemic | 2035 mg/m³ |
| Worker DNE | _, long-term | dermal | systemic | 773 |

PNEC values

| CAS No | Substance | |
|---|-----------|------------|
| Environmental compartment Value | | Value |
| 8052-41-3 stoddard solvent; Low boiling point naphtha - unspecified | | |
| Freshwater 0,14 mg/l | | 0,14 mg/l |
| Marine water 0,35 mg/l | | 0,35 mg/l |
| Freshwater sediment 1,14 mg/kg | | 1,14 mg/kg |
| Marine sediment 0,14 mg/kg | | 0,14 mg/kg |

Additional advice on limit values

Currently there are no further exposure limits available.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. Provide protection equipment (eye wash bottles, etc.).

Individual protection measures, such as personal protective equipment

Eye/face protection

Tighty fitting safety glasses with side shields. (EN 166)

Hand protection

Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Product code: beco-006 Revision date: 17.04.2023 Page 7 of 14

Suitable material: plastic and rubber (Viton.) EN 374

The exact break-through time must be obtained from the manufacturer of the protective gloves and adhered to.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Skin protection

Full cover clothing covering arms and leas.

Respiratory protection

In case of insufficient ventilation: Wear respiratory protection. (EN 143)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour: clear; yellow Odour: like: Solvent

Test method

Print date: 18.04.2023

Melting point/freezing point: No data available Boiling point or initial boiling point and >100 °C

boiling range:

Flammability: not determined Lower explosion limits: 1,0 vol. % Upper explosion limits: 8 vol. % Flash point: 23.9 °C Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: 11.2

No data available Viscosity / kinematic: Water solubility: No data available Partition coefficient n-octanol/water: No data available

Vapour pressure: 226.666 hPa calculated.

(at 37,8 °C)

Density: No data available Relative density: 0.795 Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties No data available Self-ignition temperature

> No data available Gas:

Oxidizing properties No data available

Other safety characteristics

No data available Sublimation point: Softening point: No data available No data available Pour point: No data available Viscosity / dynamic:

Further Information

VOC: 693,6 g/l (calculated.)

SECTION 10: Stability and reactivity



Safety Data Sheet

according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 8 of 14

10.1. Reactivity

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Electrostatic charges.

10.5. Incompatible materials

Oxidizing agents, strong. acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx). Irritating/poisonous gasses and vapours

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) 12500,0 mg/kg; ATE (dermal) 12222,2 mg/kg; ATE (inhalation vapour) 46,22 mg/l; ATE (inhalation dust/mist) 4,839 mg/l

| CAS No | Chemical name | | | | | | |
|-----------|--|---------------|-----------|---------|--------|--------|--|
| | Exposure route | Dose | | Species | Source | Method | |
| 2807-30-9 | 2-(propyloxy)ethanol; E | GPE | | | | | |
| | dermal | ATE mg/kg | 1100 | | | | |
| 141-43-5 | 2-aminoethanol; ethano | lamine | | | | | |
| | oral | ATE mg/kg | 500 | | | | |
| | dermal | ATE mg/kg | 1100 | | | | |
| | inhalation vapour | ATE | 11 mg/l | | | | |
| | inhalation dust/mist | ATE | 1,5 mg/l | | | | |
| 111-40-0 | 2,2'-iminodiethylamine; diethylenetriamine | | | | | | |
| | oral | LD50 mg/kg | 1553 | Rat | | | |
| | dermal | LD50 mg/kg | 1045 | Rabbit | | | |
| | inhalation vapour | ATE | 0,5 mg/l | | | | |
| | inhalation dust/mist | ATE | 0,05 mg/l | | | | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (2-aminoethanol; ethanolamine; 2,2'-iminodiethylamine; diethylenetriamine)

Carcinogenic/mutagenic/toxic effects for reproduction



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 9 of 14

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking. Causes damage to organs through prolonged or repeated exposure. (stoddard solvent; Low boiling point naphtha - unspecified)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

| CAS No | Chemical name | Chemical name | | | | | | |
|----------|----------------------------|---------------|---------------|-----------|---------------------|--------|--------|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method | |
| | Hydrocarbons, C7-C9, n-a | alkanes, iso | alkanes, cycl | ics | | | | |
| | Acute fish toxicity | LL50 mg/l | 3-10 | 96 h | Oncorhynchus mykiss | | | |
| | Acute crustacea toxicity | EL50 mg/l | 4,6-10 | 48 h | Daphnia | | | |
| 111-40-0 | 2,2'-iminodiethylamine; di | ethylenetria | mine | | | | | |
| | Acute fish toxicity | LC50 | 430 mg/l | 96 h | Poecilia reticulata | | | |
| | Acute algae toxicity | ErC50 mg/l | 1164 | 72 h | | | | |
| | Acute crustacea toxicity | EC50 | 32 mg/l | 48 h | Daphnia magna | | | |
| | Algae toxicity | NOEC | 10 mg/l | | | | | |

12.2. Persistence and degradability

No data available.

| CAS No | Chemical name | | | |
|-----------|---|-------|----|--------|
| | Method | Value | d | Source |
| | Evaluation | - | - | |
| 8052-41-3 | stoddard solvent; Low boiling point naphtha - unspecified | | | |
| | OECD 301 B | 63% | 28 | |
| | Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | | | |
| | OECD 301F | 98 | 28 | |

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|-----------|---|---------|
| 8052-41-3 | stoddard solvent; Low boiling point naphtha - unspecified | 5,01 |
| 111-40-0 | 2,2'-iminodiethylamine; diethylenetriamine | -2,13 |



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 10 of 14

BCF

| CAS No | Chemical name | BCF | Species | Source |
|--------|---|-------|---------|--------|
| | stoddard solvent; Low boiling point naphtha - unspecified | 39,66 | | |

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not discard content/container with household waste and forward for disposal according to regional/national guidelines.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - residues/unused products

040214 WASTES FROM THE LEATHER, FUR AND TEXTILE INDUSTRIES; wastes from the textile

industry; wastes from finishing containing organic solvents; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, Hydrocarbons, C7-C9, n-alkanes, isoalkanes,

cyclics)

14.3. Transport hazard class(es): 3
14.4. Packing group: III

Hazard label: 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 11 of 14

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, Hydrocarbons, C7-C9, n-alkanes, isoalkanes,

cyclics)

14.3. Transport hazard class(es): 3

14.4. Packing group:
Hazard label:
3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Hydrocarbons, C7-C9,

n-alkanes, isoalkanes, cyclics)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions: 223, 274, 955

Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Hydrocarbons, C7-C9,

n-alkanes, isoalkanes, cyclics)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics



Safety Data Sheet

according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 12 of 14

14.6. Special precautions for user

No special precautions known.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 29, Entry 40, Entry 75

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment

(SEVESO III):

Additional information: P5c

Additional information

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 [Detergents regulation]: applicable

Regulation (EC) No 850/2004 on persistent organic pollutants: not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 16.

Version 1,00 - 11.09.2017

Version 2,00 - 04.12.2018

Version 3,00 - 16.08.2022 - Change and revision of the SDS because of new information / recipe

Version 4,00 - 17.04.2023 - changes in section 2.3, 11

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act

CAS: Chemical Abstracts Service

EC: Effective Concentration

EG: European Community (Europäische Gemeinschaft)



according to Regulation (EC) No 1907/2006

#677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135

Revision date: 17.04.2023 Product code: beco-006 Page 13 of 14

EN: European Norm

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in

Bulk

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods

CLP: Classification, Labeling, Packaging

IUCLID: International Uniform Chemical Information Database

LC: Lethal concentration

LD: Lethal dose

log Kow: Octanol/water partition coefficient

MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships

OECD: Organisation for Economic Co-operation and Development

PBT: Persistent, bio-cumulative, toxic

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

TRGS: Technische Regeln für Gefahrstoffe

VOC: Volatile Organic Compounds

vPvB: very persistent and very bio-cumulative

VwVwS: Administrative Regulation for Water Pollutants

WGK: German Water Hazard Class

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

TLV: Threshold Limiting Value STOT: Specific Target Organ Toxicity

AwSV: Ordinance on Installations for Handling Substances Hazardous to Water

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| | ta acca craination metrica according to regulation (20) ito 1212/2000 [cm.] |
|-------------------------|---|
| Classification | Classification procedure |
| Flam. Liq. 3; H226 | On basis of test data |
| Acute Tox. 4; H332 | Calculation method |
| Asp. Tox. 1; H304 | Calculation method |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Dam. 1; H318 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| STOT SE 3; H336 | Calculation method |
| STOT RE 1; H372 | Calculation method |
| Aquatic Chronic 2; H411 | Calculation method |

Relevant H and EUH statements (number and full text)

| H225 | Highly flammable liquid and vapour. |
|------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| | |



Safety Data Sheet

according to Regulation (EC) No 1907/2006

| #677 Ultrasonic Non-Ammoniated Clock Cleaning Solution PCN: 135 | | |
|---|---|---------------|
| Revision date: 17.04.2023 | Product code: beco-006 | Page 14 of 14 |
| H335 | May cause respiratory irritation. | |
| H336 | May cause drowsiness or dizziness. | |
| H372 | Causes damage to organs (central nervous system) through prolonged or repeated exposure if inhaled. | |
| H372 | Causes damage to organs through prolonged or repeated exposure. | |
| H411 | Toxic to aquatic life with long lasting effects. | |
| H412 | Harmful to aquatic life with long lasting effects. | |
| EUH066 | Repeated exposure may cause skin dryness or cracking. | |
| Further Information | | |

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

asseso AG, Ottostraße 1, 63741, Aschaffenburg, Germany Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@asseso.eu, www.asseso.eu

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)