

according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TICKOPUR RW 77

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent. Special cleaner with ammonia, for the ultrasonic bath, concentrate.

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik

Street: Heinrichstr. 3 – 4

Place: 12207 Berlin, GERMANY

Telephone: +49 30 76880-280 e-mail: info@dr-stamm.de
Internet: www.dr-stamm.de

Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone 24-hours-emergency: Giftnotruf Berlin: +49 30 30686790 (german, english)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: Xi - Irritant

R phrases:

Irritating to eyes and skin.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements: Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Hazardous components which must be listed on the label

C13-C17 sek. Alkansulfonat C12-C14 Fatty alcohol ethoxylate

Ammonia ... %

Signal word: Danger Pictograms: GHS05



Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if



according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 2 of 7

present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity			
CAS No	Classification according to Directive 67/548/EEC				
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
REACH No					
213-791-2	Water	60-70 %			
7732-18-5					
270-279-3	C16-C18 fatty acid TEA	<10,0 %			
68424-19-1	Xi - Irritant R38				
	Skin Irrit. 2; H315				
	C16-C18 Fatty alcohol, ethoxylated	<10,0 %			
68920-66-1					
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	<6,0 %			
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67				
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				
	C13-C17 sek. Alkansulfonat	<6,0 %			
85711-69-9	Xi - Irritant R38-41				
	Skin Irrit. 2, Eye Dam. 1; H315 H318				
257-573-7	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt	<4,0 %			
51981-21-6					
	C12-C14 Fatty alcohol ethoxylate	<3,0 %			
68439-50-9	Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R22-41-50				
	Acute Tox. 4, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 1); H302 H318 H400				
215-647-6	Ammonia %	<5,0 %			
1336-21-6	C - Corrosive, N - Dangerous for the environment R34-50				
007-001-01-2	Skin Corr. 1B, Aquatic Acute 1 (M-Factor = 1); H314 H400				
	· · · · · · · · · · · · · · · · · · ·				

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated clothing.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of Water and soap.

After contact with eves

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case



according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 3 of 7

of troubles or persistent symptoms, consult an opthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective clothing.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special technical protective measures are necessary.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. explosive.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DR·H·STAMM

Safety Data Sheet

GmbH Chemische Fabrik according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 4 of 7

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work.

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material: PE (polyethylene). CR (polychloroprenes, Chloroprene rubber). NBR (Nitrile rubber).

Butyl rubber. FKM (Fluoroelastomer (Viton)). Tested protective gloves are to be worn: EN 374

Skin protection

Skin protection: not required.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: clear, light yellow
Odour: like: Ammonia

Test method

pH-Value (at 20 °C): 11,1 (conc.) 9,9 (1 %) DGF H-III 1

Changes in the physical state

Melting point:
-6 °C
Initial boiling point and boiling range:
>100 °C
Flash point:

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Density (at 20 °C): 1,03 g/cm³ DIN 12791

Water solubility: complete miscible

SECTION 10: Stability and reactivity

10.1. Reactivity

Exothermic reactions with: acid, concentrated.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

Revision No: 1,03 GB - EN Revision date: 04.05.2015

DR·H·STAMM GmbH Chemische Fabrik

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 5 of 7

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.

10.5. Incompatible materials

acid, concentrated.

10.6. Hazardous decomposition products

None, in case of proper use.

Further information

Do not mix with other products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
68920-66-1	C16-C18 Fatty alcohol, ethoxylated					
	oral	LD50	>2000 mg/kg	Ratte		
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt					
	oral	LD50	>2000 mg/kg		EC B.1	
	dermal	LD50	>2000 mg/kg		OECD 402	
	inhalative (4 h) vapour	LC50	4,2 mg/l		OECD 403	
68439-50-9	C12-C14 Fatty alcohol ethoxylate					
	oral	ATE	500 mg/kg			

Irritation and corrosivity

Risk of serious damage to eyes. Irritant effect on the skin: irritant.

Sensitising effects

no danger of sensitization.

SECTION 12: Ecological information

12.1. Toxicity

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge. due to the alkaline character of the product, usually, it has to be neutralized before contaminated effluents are introduced into the waste water treatment system.

CAS No	Chemical name							
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source		
51981-21-6	-6 N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt							
	Acute fish toxicity	LC50	>100 mg/l	96 h	Oncorhynchus mykiss	OECD 203		
	Acute algae toxicity	ErC50	>100 mg/l	72 h	Desmodesmus subspicatus	OECD 201		
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnien	OECD 202		
	Acute bacteria toxicity g O2/g (mg/l)				OECD 209			
1336-21-6	Ammonia %							
	Acute fish toxicity	LC50	0,53 mg/l	96 h	Onchorhynchus mykiss			
	Acute crustacea toxicity	EC50	24 mg/l	48 h	Daphnia magna			

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of

DR·H·STAMM GmbH Chemische Fabrik

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 6 of 7

the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt	<0
1336-21-6	Ammonia %	-1,38

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 5,9 % (60,77 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Data changed from previous versions: 2, 8, 11, 12, 15, 16

Relevant R-phrases (Number and full text)

- Highly flammable.
 Harmful if swallowed.
 Causes burns.
 Irritating to eyes.
 Irritating to skin.
- Risk of serious damage to eyes.
 Very toxic to aquatic organisms.

Revision No: 1,03 GB - EN Revision date: 04.05.2015



according to Regulation (EC) No 1907/2006

TICKOPUR RW 77

Print date: 04.06.2015 No: 83029 Page 7 of 7

67 Vapours may cause drowsiness and dizziness.

Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life.

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

 Revision No: 1,03
 GB - EN
 Revision date: 04.05.2015